

IL-10,632

DIELECTROPHORETIC CONCENTRATION OF PARTICLES UNDER ELECTROKINETIC FLOW

BY

Robin R. Miles (USA)
80 Kendall Lane
Danville, Ca 94526

Kerry A. Bettencourt (USA)
11873 West Vomac Road
Dublin, CA 94568

Christopher K. Fuller (USA)
1145 Hillcrest Ct.
Livermore, CA 94550

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

DIELECTROPHORETIC CONCENTRATION OF PARTICLES
UNDER ELECTROKINETIC FLOW

The United States Government has rights in this invention pursuant to Contract No. W-7405-ENG-48 between the United States Department of Energy and the University of California for the operation of Lawrence Livermore National Laboratory.

BACKGROUND OF THE INVENTION

5 The present invention relates to the concentration of particles in microfluidic devices, particularly to the use of dielectrophoresis to collect or concentrate the particles, and more particularly to the use of dielectrophoresis to collect particles under the conditions of electrokinetically-driven flow.

10 Microfluidic devices are most useful when operating with small sample volumes. Small sample volumes result in increased reaction times and reduced reagent use which means significantly reduced costs for the multitude of tests that one desires to conduct on any given sample. Dielectrophoretic concentration of the samples is a useful method for achieving these goals. Dielectrophoresis is attractive on the microfluidic scale because the forces
15 become significant and useful at dimensions of less than 1 mm. Electrokinetic/electroosmotic flow is also useful in these devices because it obviates the need for micropumps and microvalves.

The present invention involves the combination of dielectrophoresis (DEP) and electrokinetic/electroosmotic flow. Such combination would not normally be an obvious choice since one might think that the two electric fields and their associated double charge layers may interfere with each other. Also, dielectrophoresis collection works best in the slow boundary-layer flow normally associated with pressure-driven flow. However, by the present invention, it has been found that particles can still collect even in the more uniform flow field associated with electroosmotic flow. The 5-10 mm double charge layer associated with establishing electroosmotic flow does not interfere, or be interfered with, by the DEP field in a significant way.

SUMMARY OF THE INVENTION

It is an object of the present invention to collect particles in a microfluidic channel using dielectrophoresis.

A further object of the invention is to provide for dielectrophoretic concentration of particles under electrokinetic flow.

Another object of the invention is to use dielectrophoresis to collect particles under the conditions of electrokinetically-driven flow.

Another object of the invention is to use a combination of dielectrophoresis and electrokinetic/electroosmotic flow for the collection of particles in a microfluidic device.

Another object of the invention is to provide a microfluidic device capable on dielectrophoretic concentration of particles under electrokinetic flow.

Other objects and advantages of the present inventions will become apparent from the following description and accompanying drawing. Basically the present invention involves a method and apparatus for collecting or concentrating particles in a microfluidic channel using dielectrophoresis under conditions of electrokinetically-driven flow. This is accomplished by interdigitated electrodes patterned on the inner surface of a microfluidic channel, preferable formed of glass, applying a DC voltage across the ends of the channel to initiate an electrokinetic/electroosmotic flow field, and applying an AC voltage across the interdigitated electrodes to set up a non-uniform electric field capable of trapping particles using the dielectrophoretic force. The trapped particles are released upon removal of the voltage to the electrodes.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated into and form a part of the disclosure, illustrate an embodiment of the invention and, together with the description, serve to explain the principles of the invention.

Figure 1 is a schematic illustration of a microfluidic electrokinetic flow channel with interdigitated electrodes located along the length of the channel.

Figure 2 is a greatly enlarged top view of the interdigitated electrodes of Figure 1 and AC power source therefor.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is directed to dielectrophoretic concentration of particles under electrokinetic flow. The present invention involves a method and apparatus for collecting particles in a microfluidic channel using the combination of dielectrophoresis and electrokinetic/electroosmotic flow. Electrokinetically-driven flow is an important technique for moving fluids and sample around a

microfluidic bio-chemical assay chip, and the combination with the advantages of dielectrophoretic manipulation in this regime significantly advances this field of technology.

Figures 1 and 2 schematically illustrate an embodiment of an apparatus for carrying out the present invention, with Figure 2 being a top view of a pair of interdigitated electrodes of Figure 1. Interdigitated electrodes are patterned on the inner surface of a microfluidic channel but can be suspended within the fluid. Glass is the preferred material for the microfluidic channel because it promotes electroosmotic flow, particularly if preconditioned with sodium hydroxide. However, other materials, such as certain types of plastics may be utilized. A direct current (DC) voltage is applied across the ends of the channel to initiate the electrokinetic/electroosmotic flow field. An alternating current (AC) voltage is applied across the interdigitated electrodes to set up a non-uniform electric field capable of trapping particles using the dielectrophoretic force. Particles are swept down the channel electrokinetically and are trapped within the field established by the interdigitated electrodes. The trapped particles can be released when the voltage to the interdigitated electrodes is released. Thus, this approach enables concentration of the sample prior to testing, since dielectrophoresis effects the motion on polarizable particles within a non-uniform electric field. Positive dielectrophoresis can be used to concentrate particles in areas of high electric field gradients, and can be used to eliminate the use of centrifuging to concentrate biological samples. Negative dielectrophoresis can be used to discriminate between various types of biological particles.

Referring now to the drawings, a microfluidic device generally indicated at 10 includes at least one microfluidic channel 11, having a pair of spaced sets of

interdigitated electrodes generally indicated at 12 patterned on the inner surface of the channel 11, which, for example, may be formed of bonded glass plates with the channel 11 formed therein as known in the art. A DC voltage supply 13 having a positive electrode 14 and a negative electrode 15 located at opposite ends of channel 11 produces a voltage across the ends of the channel 11 to initiate an electrokinetic/electroosmotic flow field indicated by arrow 16. An AC power supply 17 provides a voltage which is applied across the electrode plates 18 and 19 of interdigitated electrodes 12, as shown in Figure 2, which set up a non-uniform electric field 20 capable of trapping particles 21 using the dielectrophoretic force. Each of electrode plates 18 and 19 include projecting legs 22-23 and 24-25, with leg 22 located intermediate legs 24 and 25 and with leg 25 been located intermediate legs 22 and 23.

It has thus been shown that the present invention provides for dielectrophoretic concentration of particles under electrokinetic flow, by using at least one set of interdigitated electrodes patterned on the inner surface of a microfluidic channel. Particles swept down the channel electrokinetically are trapped within the field established by the interdigitated electrodes. Thus, the apparatus can be used to concentrate the sample prior to testing due to the combined use of dielectrophoresis and electrokinetic/electroosmotic flow. While only one microfluidic channel has been shown, the present invention can be applied to microfluidic devices having a number of channels.

While a particular embodiment has been illustrated and described to exemplify and teach the principles of the invention, such is not intended to be limiting. Modifications and changes may become apparent to those skilled in the art, and it is intended that the invention be limited only by the scope of the appended claims.